



Meet Your Filtration Needs Is Our Goal.

SS-UE008-4333

UF Membrane for Pharmaceutical, Biological, Food and Dairy Applications

PRODUCT DESCRIPTION

| | |
|----------------------------|---------------------------------------------------------------------------|
| Membrane Chemistry: | Proprietary semi-permeable polyethersulfone (PES) |
| Membrane MWCO: | 8,000 Daltons |
| Construction: | Sanitary spiral wound element with net outer wrap |
| | Feed Spacer: F=31 mil, G=46 mil, H=65 mil |
| Options: | Outer wrap: N= Control Bypass without Tail T= Control Bypass with Tail |

SPECIFICATIONS

| Model | Active Membrane Area | | |
|---------------|-----------------------------------|-----------------------------------|-----------------------------------|
| | FN/T Spacer (31mil) | GN/T Spacer (46mil) | HN/T Spacer (65mil) |
| | ft ² (m ²) | ft ² (m ²) | ft ² (m ²) |
| SS-UE008-4333 | 89 (8.2) | 73 (6.7) | 54 (5.0) |

Specialty feed spacer is available.

OPERATION SPECIFICATIONS


| | |
|--------------------------------------|--------------------------|
| Typical Operation Pressure: | 30-120 psi (2.1-8.3 bar) |
| Maximum Operation Pressure: | 140 psi (9.7 bar) |
| Operating Temperature Range: | 41-122°F (5-50°C) |
| Cleaning Temperature Range: | 105-122°F (40-50°C) |
| pH-Continuous Operation @25°C | 2.0-10.0 |
| pH-CIP @25°C | 1.8-11.0 |

Contact us for specific applications.

DESIGN PARAMETERS

| | |
|------------------------------------------|----------------------------------|
| Feed: | F spacer: 22-29 gpm |
| | G spacer: 29-36 gpm |
| | H spacer: 33-42 gpm |
| Design Pressure Drop Per Element: | F spacer: 12-15 psi (0.8-1.0bar) |
| | G spacer: 15-20 psi (1.0-1.4bar) |
| | H spacer: 15-25 psi (1.0-1.7bar) |

DIMENSIONS



| Model | A inches (mm) | B inches (mm) | C inches (mm) |
|---------------|------------------|------------------|------------------|
| SS-UE008-4333 | 33.0 (838) | 4.3 (109) | 0.831 (21.1) |

RisingSun Membrane Technology (Beijing) Co., Ltd. www.risingsunmem.com

Add: Building 2, Shunren Road No.51, Linhe Industrial Zone, Shunyi District, Beijing, China Post Code: 101300

Tel: 86-10-89496869 Fax: 86-10-89496839 Mail: info@risingsunmem.com